

CRICKET - D 100 CK



CRICKET "CK"



For illustrative purposes only

ENGINE

Engine brand	DEUTZ
Engine model	BF4M1013EC
Cylinders	4
Speed	1500 r.p.m.
Cubic capacity	4.80 l
Air intake	Turbocharged
Standard voltage	12 Vdc
Sae	3-11½
BMEP	1713 kPa
Cooling	Water
Flywheel P.R.P. Power	92.8 kW
Flywheel Stand-by Power	97.8 kW
Fuel Cons. at 100% (L.T.P.)	25.7 l/h
Fuel Cons. at 100% (P.R.P.)	24.2 l/h
Fuel Cons. at 75% (P.R.P.)	18.3 l/h
Fuel Cons. at 50% (P.R.P.)	12.8 l/h
Fuel Cons. at 25% (P.R.P.)	7.7 l/h
Electronic regulator	On request
Precision class	A1
Oil quantity	13.0 l
Engine Antifreeze capacity	7.2 l
Radiator type	Tropical
Heat from radiator	65.8 kW
Heat from exhaust	68.8 kW
Heat from radiation	0.0 kW
Exhaust temperature	490 °C
Cooling air flow	90.00 m ³ /min
Combustion air flow	0.00 m ³ /min
Exhaust gas flow	16.75 m ³ /min
TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Stage 2

MAIN DATA

Continuous power (PRP)	100.0 (kVA)
Continuous power (PRP)	80.0 (kW)
Stand-by power (LTP)	110.0 (kVA)
Stand-by power (LTP)	88.0 (kW)
Voltage • Frequency • Power Factor	400V • 50Hz • 0.8 cosφ
Sound pressure 7 m.	78.0 dBA

DIMENSIONS AND WEIGHT

Width	1100 mm
Length	2620 mm
Height	1480 mm
Weight	1460 kg

ALTERNATOR

Alternator brand	STAMFORD
Alternator model	UCI274C
P.R.P. Power	100.0 kVA
L.T.P. Power	110.0 kVA
Connection	Series star
Phases	3PH+N
Winding	12 terminals Winding 311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	AS440
Precision	1.0 ± %

BASEFRAME

Model	CK30
Standard tank	145 l
Optional tank	0 l
Oversized tank*	0 l

CANOPY & SILENCER

Canopy model	CK30
Silencer model	F60/00
Silencer outlet diameter	60.0 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.
L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

